

US009408984B2

(12) United States Patent

Durack et al.

(10) Patent No.: US 9,408,984 B2

(45) **Date of Patent:**

Aug. 9, 2016

(54) SELF-INJECTION DEVICE

(75) Inventors: David T. Durack, Durham, NC (US);

Artis R. Lockhart, Durham, NC (US); Lawrence A. Monahan, Willow

Springs, NC (US)

(73) Assignee: Becton, Dickinson and Company,

Franklin Lakes, NJ (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 267 days.

(21) Appl. No.: 13/261,212
(22) PCT Filed: Sep. 15, 2009

(86) PCT No.: PCT/US2009/005148

§ 371 (c)(1), (2), (4) Date:

May 25, 2012

(87) PCT Pub. No.: WO2011/034516

PCT Pub. Date: Mar. 24, 2011

(65) Prior Publication Data

US 2012/0245558 A1 Sep. 27, 2012

(51) **Int. Cl.**

 A61M 5/32
 (2006.01)

 A61M 5/28
 (2006.01)

 A61M 5/46
 (2006.01)

(52) U.S. Cl.

(58) Field of Classification Search

USPC 604/110, 185, 187, 192, 197, 198, 117 See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

1,288,174 A 12/1918 Pittenger 2,667,165 A 1/1954 Smith (Continued)

FOREIGN PATENT DOCUMENTS

EP 0258073 6/1987 EP 0749 758 A1 12/1996 (Continued)

OTHER PUBLICATIONS

Japanese Office Action dated Aug. 20, 2013 issued by the Japanese Patent Office in counterpart Japanese Application No. 2012-529720. (Continued)

Primary Examiner — Aarti B Berdichevsky
Assistant Examiner — Laura Schell
(74) Attorney, Agent, or Firm — Dickinson Wright PLLC

(57) ABSTRACT

A self-injection device (101) for delivering a medicament includes a housing (111), and a needle (103) connected to the housing (111). A compressible reservoir (121) is connected to the housing (111) and is in fluid communication with a needle (103) such that compressing the reservoir (121) delivers medicament from the reservoir (121) to the needle (103) and moves the needle (103) from the first position to the second position. A platform (171) is disposed within the housing (111) about which the housing (111) is rotatable between a plurality of positions. Each of the positions corresponds to a different distance the needle (103) is moved to the second position during an injection to provide a variable injection depth. The needle (103) is withdrawn into the housing (111) after an injection without requiring manual manipulation by the user, thereby preventing needle sticks and other accidents.

20 Claims, 6 Drawing Sheets

